

CRANKCASE	SAE 15W-40 38 + 6 qts.	SAE 15W-40 38 + 6 qts.	SAE 15W-40 36 + 8 qts.	SAE 15W-40 36 + 8 qts.	SAE 15W-40 36 + 8 qts.	SAE 15W-40 36 + 8 qts.	SAE 15W-40 23 + 2 qts.	SAE 15W-40 25 + 2 qts.	SAE 15W-40 23 + 2 qts.	SAE 30 24 + 12 qts.
TRANSMISSION	SAE 50 6 gallons	SAE 50 6 gallons	SAE 50 5.1 gallons	SAE 50 5.1 gallons	SAE 50 5.1 gallons	SAE 50 5.1 gallons	Dextron II 8 gallons	Dextron II 35 quarts	Dextron II 8 gallons	SAE 90 17 pints
PUMP TRANSMIS.	Dextron II 24 pints	Dextron II 24 pints	Dextron II 22 pints	Dextron II 22 pints	Dextron II 22 pints	Dextron II 22 pints	Dextron II 22 pints	SAE 90-140 AR	Dextron II 22 pints	SAE 90 4.5 quarts
DIFFERENTIAL	SAE 90-140 47 pints	SAE 90-140 47 pints	SAE 90-140 43 pints	SAE 90-140 43 pints	SAE 90-140 28 pints	SAE 90-140 28 pints	SAE 90-140 28 pints	SAE 90-140 28 pints	SAE 90-140 28 pints	SAE 90-140 28 pints
POWER STEERING	SAE 10W AR	SAE 10W AR	SAE 10W AR	SAE 10W AR	SAE 10W AR	SAE 10W AR	Dextron II AR	Dextron II AR	ATF AR	Dextron 2 quarts
WATER TANK	500 gallons	500 gallons	500 gallons	500 gallons	500 gallons	500 gallons	500 gallons	500 gallons	500 gallons	500 gallons
ENGINE	Cummins	Cummins	Cummins	Cummins	Cummins	Cummins	Detroit	Detroit	Detroit	Cummins
MODEL	N14-370	N14-370	NTC-400	NTC-400	NTC-400	NTC-400	8V71TA	8V71TA	8V71TA	NTA-400
HORSEPOWER	370	370	400	400	400	400	370	370	350	370
CU ³ /CYLIND	855	855	855	855	855	855	568	568	568	855
TRANSMISSION	Spicer PS145-7A	Spicer PS145-7A	Spicer SST-2	Spicer SST-2	Spicer SST-2	Spicer SST-2	Allison	Allison	Allison	Spicer SST-2
MAIN PUMP	Waterous	Waterous	Waterous	Waterous	Waterous	Waterous	Waterous	Hale	Waterous	Hale
PUMP CAPACITY	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI	1500 GPM @150 PSI
PRIMING PUMP	Waterous	Waterous	Waterous	Waterous	Waterous	Waterous	Waterous	Hale	Waterous	Hale
PRIME PUMP TYPE	Rotary Vane	Rotary Vane	Rotary Vane	Rotary Vane	Rotary Vane	Rotary Vane	Rotary Vane	Rotary Vane	Rotary Vane	Elec. Impeller
RELIEF VALVE	Waterous	Waterous	Waterous	Waterous	Waterous	Waterous	Waterous	Hale	Waterous	Hale
RELIEF VL. RANGE	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft	50 Suction 75-300 TK/Drft
ENGINE TEMP.	180-200	165-195	160-190	160-190	160-190	160-185	160-185	160-185	160-185	160-200
OIL PRESSURE	10, 35-45	10, 35-45	10, 35-45	10, 35-45	10, 35-45	10, 35-45	25-30	25-30	25-30	30, 40-75
COOL ENGINE AT							900-1000 RPM	900-1000 RPM	900-1000 RPM	
STARTER MOTOR	12 Volt	12 Volt	12 Volt	12 Volt	12 Volt	12 Volt	24 Volt	24 Volt	24 Volt	12 Volt
ALTERNATOR	160 Amp.	160 Amp.	160 Amp.	160 Amp.	140 Amp.	140 Amp.	160 Amp.	160 Amp.	140 Amp.	100 Amp.
OPER. RANGE	1100-1600	1100-1600	1350-2100 1900	1350-2100 1900	1350-2100 1800-1900	1350-2100 1800-1900	1900 RPM	1900 RPM	1900 RPM 1900	1700-2200
SHIFT AT	1800-1900	1800-1900	2100 RPM	2100 RPM	2100 RPM	2100 RPM	1900 RPM	1900 RPM	1900 RPM	2200 RPM
TRANSMIS. TEMP							160-220	160-220	160-220	
DISCONTINUE OP.							250	250	300	
PROLONGED IDLE	900-1100	900-1100	900-1100	900-1100	900-1100	900-1100	800	800	800	
PUMP GEAR	7th	7th	6th	6th	6th	6th	1- 4	1- 4	1- 4	6th
COMPRESSOR			14'	14'	14'	14'	16'	16'	15.5'	
WATER PUMP	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100	100 @ 2100
BRAKE TYPE	MGM	MGM	MGM	Anchor	Anchor	Anchor	Anchor	Anchor	Anchor	
BRAKE PSI	90	90	90	90	90	90	90	90	90	90
MIN. BRAKE PSI	90	90	90	90	90	90	80	80	90	80
TRANSFER VALVE	Any	Any	Any	< 100 Electric	< 100 Electric	75	30			< 70
DRAFT RPM'S							1300-1500 RPM			1000-1200 RPM
AIR TANKS	1+ 5	1+ 4	1+ 3	1+ 3	1+ 3	1+ 3	1+ 3	1+ 3	1+ 3	1+ 3
<i>FLEA</i> v1.0 07.97	1996 SEAGRAVE	1993 SEAGRAVE	1990 SEAGRAVE	1988 SEAGRAVE	1986 SEAGRAVE	1984 SEAGRAVE	1982 VAN PELT	1982 SEAGRAVE	1980 SEAGRAVE	1976 WARD